







**04C 10T 10Teeth Pitch 6.35mm 1/4" Bore 6mm 7mm 8mm Industry Transmission Driving Single Sprockets engine for motor high quality**

**Item specifics:**

Material:Steel  
 Standard:ISO  
 Model Number:04C-10F  
 Series:04C  
 Pitch:6.35mm, 1/4 inch  
 Gear Number:10 Teeth  
 Gear Width(mm):2.8  
 Overall Width(mm):16  
 Bore Dimmeter:6mm 7mm 8mm  
 Tighten Screws:2xM6 (free send allen key)  
 Net Weight:0.03 Kg  
 Materials :45# Steel, Heat treatment

The sprocket hole precision, has been equipped with a tight top screw, the use of super-convenient

Steel Sprockets and Chain Specification List										
			Standard Processing (Without tighten screws)			Fine Processing (With tighten screws)				
										
节距 Pitch	型号 Model	齿数 Gear Number	外形尺寸 Dimension (mm)					Net Weight (Kg)	备注 Remark	
			齿宽 Gear Width H	总厚 Overall Width L	凸台 Plate Dia. D	内孔 Bore Dia. C	分度圆 P Circle Dia. A			
for 04C Chain Pitch=6.35mm=1/4" 	04C-10F	10	2.8	16	16	6.7	8	20.5	0.03	Fine Processing (with tighten screws)
	04C-15F	15			23	6.7	8	30.5	0.05	
	04C-20F	20			33	8	40.6	0.12		
	04C-30F	30			50	10	60.7	0.25		
	04C-10	10			16	6	20.5	0.03		
	04C-13	13			21	6	26.5	0.05		
	04C-15	15			25	6	30.5	0.07		
	04C-20	20			33	8	40.6	0.12		
	04C-25	25			38	8	50.6	0.2		
	04C-30	30			50	8	60.7	0.25		
	04C-35	35			50	10	70.8	0.28		
	04C-40	40			55	10	80.8	0.35		
04C-50	50	60	10	101.1	0.5					
Supply Chain: Peremeter 508mm/20inch, 80Links. 5080mm/200inch, 800links. We have 04C 16Teeth Tensioner Sproket										
for 06B Chain Pitch=9.525mm=3/8" 	06B-10	10	5	20	20	10	30.8	0.06	Standard Processing (without tighten screws)	
	06B-15	15			32	10	45.8	0.16		
	06B-18	18			40	10	54.8	0.25		
	06B-25	25			48	12	75.8	0.42		
	06B-30	30			24	50	12	91.1		0.5
	06B-40	40			26	60	16	121.4		0.85
	06B-50	50			70	16	151.7	1.2		
Supply Chain: Peremeter 1524mm/60inch, 160Links										
for 08B Chain Pitch=12.7mm=1/2" 	08B-10	10	7	22	26	10	40.4	0.11		
	08B-13	13			35	10	52.6	0.2		
	08B-16	16			45	12	64.7	0.35		
	08B-20	20			54	12	81.2	0.55		
	08B-30	30			27	65	16	121.4		1.1
	08B-40	40			30	78	16	161.8		1.85
Supply Chain: Peremeter 1524mm/60inch, 120Links										
<b>Remarks:</b> When choose Standard Processing sprockets, please attention, Bore Diameter maybe not same as list, please subject to the model detail page, it's without tighten screws, it need process Key-Way or screw hole, if need us process contact us(PROCESS MOQ. is 5pcs, need exceed fee), aslo provide bore Dia. extend.										