

04C 20T 20Teeth Pitch 6.35mm 1/4" Bore 8mm Industry Transmission Drive gear Single Sprockets DIY engine for motor roller chain

Item specifics:

Material:Steel
 Standard:ISO
 Model Number:04C-20F
 Series:04C
 Pitch:6.35mm, 1/4 inch
 Gear Number:20 Teeth
 Gear Width(mm):2.8
 Overall Width(mm):16
 Bore Dimmeter: 8mm
 Tighten Screws:2xM6 (free send allen key)
 Net Weight:0.12 Kg
 Materials :45# Steel Heat treatment

The sprocket hole precision, has been equipped with a tight top screw, the use of super-convenient

Steel Sprockets and Chain Specification List										
			Standard Processing (Without tighten screws)		Fine Processing (With tighten screws)					
节距 Pitch	型号 Model	齿数 Gear Number	外形尺寸 Dimension (mm)					Net Weight (Kg)	备注 Remark	
			齿宽 Gear Width H	总厚 Overall Width L	凸台 Plate Dia. D	内孔 Bore Dia. C	分度圆 P Circle Dia. A			
for 04C Chain Pitch=6.35mm=1/4" 	04C-10F	10	2.8	16	16	6.7	8	20.5	0.03	Fine Processing (with tighten screws)
	04C-15F	15			23	6.7	8	30.5	0.05	
	04C-20F	20			33	8	40.6	0.12		
	04C-30F	30			50	10	60.7	0.25		
	04C-10	10			16	6	20.5	0.03		
	04C-13	13			21	6	26.5	0.05		
	04C-15	15			25	6	30.5	0.07		
	04C-20	20			33	8	40.6	0.12		
	04C-25	25			38	8	50.6	0.2		
	04C-30	30			50	8	60.7	0.25		
	04C-35	35			50	10	70.8	0.28		
	04C-40	40			55	10	80.8	0.35		
04C-50	50	60	10	101.1	0.5					
Supply Chain: Peremeter 508mm/20inch, 80Links. 5080mm/200inch, 800links. We have 04C 16Teeth Tensioner Sproket										
for 06B Chian Pitch=9.525mm=3/8" 	06B-10	10	5	20	20	10	30.8	0.06	Standard Processing (without tighten screws)	
	06B-15	15			32	10	45.8	0.16		
	06B-18	18			40	10	54.8	0.25		
	06B-25	25			48	12	75.8	0.42		
	06B-30	30			24	50	12	91.1		0.5
	06B-40	40			26	60	16	121.4		0.85
	06B-50	50			70	16	151.7	1.2		
Supply Chain: Peremeter 1524mm/60inch, 160Links										
for 08B Chian Pitch=12.7mm=1/2" 	08B-10	10	7	22	26	10	40.4	0.11		
	08B-13	13			35	10	52.6	0.2		
	08B-16	16			45	12	64.7	0.35		
	08B-20	20			54	12	81.2	0.55		
	08B-30	30			27	65	16	121.4		1.1
	08B-40	40			30	78	16	161.8		1.85
Supply Chain: Peremeter 1524mm/60inch, 120Links										
Remarks: When choose Standard Processing sprockets, please attention, Bore Diameter maybe not same as list, please subject to the model detail page, it's without tighten screws, it need process Key-Way or screw hole, if need us process contact us(PROCESS MOQ. is 5pcs, need exceed fee), aslo provide bore Dia. extend.										