

**specifics**

Efficiency:IE 2  
 Voltage(V):dc 12-36V  
 Type:Gear Motor  
 Protect Feature: Explosion-proof  
 Usage:Car,Electric Bicycle  
 Certification:CE,ROHS

**Specifications**

1.Standard Operating Conditions

1-1 Rated Voltage:**24V**

1-2 Direction of Rotation:**CW** when viewed from output shaft side

1-3Operating Temperature and Humidity:Temperature range of **-10C~+50C**,Humidity range of **30%~80%**.

1-4Storage Temperature:Temperature range of **-20C~+60C**

2.Measuring Conditions:

2-1Motor Position:To be place t horizontally when measuring

2-2Power Supply: Regulated DC power supply

--Robotics, Small Appliance, Fanner, Electric Curtain;

--Medical Pump, Surgery Tools, Medical Stirrer, centrifugal Machine; Electric Valve, Actuator, medical device

--Electric motor,low noise,low current and no spark.

**parameter:**

Voltage		Noload		At Max. Efficiency				Stall		Speedreducer	Weight	
使用範圍	額定值	轉速	電流	轉速	電流	扭矩	功率	扭矩	電流	減速比	長度	单位
Using	The	Speed	Current	Speed	Current	Torque	Power	Torque	Current	Redctio n	(L) Size	
Rangge	Rated	r/min	ma	r/min	A	kg. cm	W	kg. cm	A	Ratio	mm	约g
6-30V	24V	12	135	9	0.35	60	15	禁止	3	506	29	280

